


K-9S

高圧洗浄タイプ スプレーノズル



管径 in	寸 法 A	寸 法 B	重量 g
1/4	22	10	20
3/8	25	11	31

※記載の数値は代表値であり、保証値ではありません。

35°

管径 in	本体穴 mm	水 量 L/min / Spray 角 度												
		水圧 (MPa) (kg/cm ²)	0.029 0.3	0.049 0.5	0.069 0.7	0.098 1.0	0.147 1.5	0.196 2.0	0.245 2.5	0.294 3.0	0.392 4.0	0.490 5.0	0.735 7.5	0.980 10.0
1/4	4.0				2.70/18°	3.30/25°	4.00/25°	4.60/30°	5.15/35°	5.60/35°	6.58/35°	7.40/40°	9.10/40°	10.30/40°
	5.0				3.80/18°	4.60/25°	5.50/25°	6.30/30°	7.10/35°	7.80/35°	9.00/35°	10.10/40°	12.40/40°	14.40/40°
	6.4		4.10/15°	4.90/18°	5.50/20°	6.40/25°	7.90/30°	9.30/35°	10.50/35°	11.50/35°	13.40/35°	15.10/40°	18.40/40°	21.00/40°
	7.0		5.70/15°	6.70/18°	7.50/20°	8.70/25°	10.70/30°	12.40/35°	14.00/35°	15.40/35°	17.90/35°	20.00/40°	24.50/40°	27.80/40°
3/8	7.0		5.70/15°	6.70/18°	7.50/20°	8.70/25°	10.70/30°	12.40/35°	14.00/35°	15.40/35°	17.90/35°	20.00/40°	24.50/40°	27.80/40°
	8.0		7.00/15°	8.40/18°	9.80/20°	11.70/25°	14.10/30°	16.00/35°	17.70/35°	19.50/35°	22.50/35°	25.00/40°	31.00/40°	35.50/40°
	9.0		8.00/15°	10.80/18°	13.00/20°	15.40/25°	18.90/30°	21.70/35°	24.50/35°	26.70/35°	31.70/35°	35.60/40°	43.00/40°	49.00/40°
	11.0		11.50/15°	14.60/18°	16.70/20°	20.10/25°	24.30/30°	28.20/35°	31.20/35°	34.30/35°	38.50/35°	42.40/40°	51.20/40°	58.00/40°