


K-12

直進タイプ スプレーノズル



管径 in	寸 法 mm		重量 g
	A	B	
1/4	20	10	15

※記載の数値は代表値であり、保証値ではありません。

管径 in	吹出穴 mm	水 量 L/min / Spray 角 度													
		水圧 (MPa) (kg/cm ²)	0.0196 0.2	0.029 0.3	0.049 0.5	0.069 0.7	0.098 1.0	0.147 1.5	0.196 2.0	0.245 2.5	0.294 3.0	0.392 4.0	0.490 5.0	0.686 7.0	0.980 10.0
1/4	2.0		—	—	1.60/40°	1.90/45°	2.45/50°	3.20/55°	3.60/55°	3.90/55°	4.20/55°	4.63/50°	5.00/50°	6.00/50°	6.50/45°
	2.4			1.60/40°	2.00/45°	2.40/50°	2.90/55°	3.60/55°	4.30/60°	4.90/60°	5.40/60°	6.20/55°	6.90/50°	8.20/50°	9.40/45°
	2.6		1.80/45°	2.20/40°	2.70/55°	3.10/55°	3.65/60°	4.45/60°	5.20/60°	5.90/60°	6.50/60°	7.50/60°	8.40/50°	10.05/50°	11.40/50°
	3.2		2.60/45°	3.00/50°	3.80/55°	4.40/55°	5.20/60°	6.40/60°	7.40/60°	8.20/60°	8.80/60°	10.00/60°	11.00/50°	13.20/50°	14.80/50°