



The image shows a technical drawing of a mechanical assembly, likely a frame or support structure, with two views: a front view on the left and a side view on the right.

Front View (Left):

- Overall width: 630 (between vertical supports) + 50 (left flange) + 50 (right flange) = 730.
- Overall height: 740.
- Vertical dimensions from bottom: 25 (base), 170 (lower section), 30 (middle section), 440 (upper section), 70 (top flange), and 30 (top plate).
- Callouts: 1 (top plate), 2 (left vertical support), 3 (right vertical support), 4 (bottom right corner), 5 (bottom left corner).

Side View (Right):

- Overall width: 448 (between vertical supports) + 26 (left flange) + 26 (right flange) = 500.
- Overall height: 740 (same as front view).

均等耐荷重 350 kg

カンヌキは前後194ミリピッチで移動可能

5	カンヌキ	1	SPCC-SD	1.2t	
4	アジャスター	4	ABS・ユニクロメッキ	M12XP1.75	
3	脚フレーム	2			
2	天受フレーム	2	SPCC-SD	1.2t	
1	天板	1	品番ニヨリ異なる(上記参照)		
品番	部 品 名	1台分 数 量	材 質	備 考	
作成	H29.1.23	3角法	名 称	軽量作業台	
承認	設 計	製 図		尺 度	K Sタイプ カブセ天板仕様
					W900×D600×H740
		網島		1:12	外觀図
 株式会社 サカエ			図 番	葉 番	