


RoHS10 Support

REACH Support

CFSI Support

○形状 (SHAPE)



○規格 (Standard)

JIS-C-5410

○仕様 (Specification)

特性インピーダンス (Impedance): 50 Ω

定格周波数 (Working Frequency Range): DC~6GHz

電圧定在波比 (VSWR): ≤1.30 at 6GHz

挿入損失 (Insertion Loss): 0.05dB max × √f GHz (f:Frequency)

定格電圧 (Voltage Rating): 335V rms

耐電圧 (Proof Voltage): 800V rms

接触抵抗 (Contact Resistance): 5m Ω max

絶縁抵抗 (Insulation Resistance): ≥5000M Ω

勘合保証回数 (Connector Life): 500 times min


推奨締め付けトルク (Recommended Torque) 0.8~1.1 Nm



4	FERRULE	BRASS	NICKEL
3	Contact	BeCu	GOLD
2	Dielectric	PTFE	NONE
1	Body	BRASS	GOLD
No	DESCRIPTION	MATERIAL	FINISH


○加工寸法 (ASSEMBLY)

RECOMMENDED CABLE STRIPPING DIMS



SOLDER CONTACT TO CABLE CENTER CONDUCTOR

RECOMMENDED CLIMPING TOOL SIZE




RECOMMENDED CRIMP HEIGHT 5.55±0.2

The tolerance in this area is ± 0.10

TOLERANCE

DECIMALS .XX ±0.10 .X ±0.15
DIAMETER .X ±0.10

Approved Checked Drawn



Unit

mm

A4

日本エレパーツ株式会社
NIHON ELEPARTS Co.,LTD

NAME

SMA-PJ-RG58U (AU)

REV

1