


RoHS10 Support

REACH Support

CFSI Support

IP67 Waterproof after mating (Before the panel)



○仕様 (Specification)

特性インピーダンス (Impedance) : 50Ω

定格周波数 (Working Frequency Range) : DC~6GHz

電圧定在波比 (VSWR) : ≤ 1.20 at 6GHz

定格電圧 (Voltage Rating) : 500V rms

耐電圧 (Proof Voltage) : Ac1.0KV

接触抵抗 (Contact Resistance) : 1mΩ max(4.3/10)、1.5mΩ max(N)

絶縁抵抗 (Insulation Resistance) : $\geq 5000\text{M}\Omega$

使用温度範囲 (Temperature Range) : -55~165°C

パッシブ相互変調 (PIM3) : $\leq -160\text{dBc}$

締め付けトルク (Tightening Torque) : 5N・m(4.3/10)、1.7N・m(N)

勤合保証回数 (Connector Life) : 100 times min



4	Contact head	P.Bronze	Silver
3	Center Contact	Beryllium	Silver
2	Dielectric	PTFE	NONE
1	Body	Brass	Termary alloy
No	DESCRIPTION	MATERIAL	FINISH

TOLERANCE DECIMALS .XX ± 0.10 .X ± 0.15 DIAMETER .X ± 0.10				日本エレパーツ株式会社 NIHON ELEPARTS Co.,LTD	
Approved	Checked	Drawn			
			Unit mm	NAME 4.3)10J-NJ	REV 1
			A4		