


K-9S

高压洗净タイプ
 スプレーノズル



管径 in	寸 法 mm		重量 g
	A	B	
¼	22	10	20
⅜	25	11	31
½	32	14	63

※記載の数値は代表値であり、保証値ではありません。

35°														
管径 in	本体穴 mm	水 量 L/min / Spray 角 度												
		水压 (MPa)	0.029	0.049	0.069	0.098	0.147	0.196	0.245	0.294	0.392	0.490	0.735	0.980
		(kg/cm ²)	0.3	0.5	0.7	1.0	1.5	2.0	2.5	3.0	4.0	5.0	7.5	10.0
¼	4.0				2.70/18°	3.30/25°	4.00/25°	4.60/30°	5.15/35°	5.60/35°	6.58/35°	7.40/40°	9.10/40°	10.30/40°
	5.0				3.80/18°	4.60/25°	5.50/25°	6.30/30°	7.10/35°	7.80/35°	9.00/35°	10.10/40°	12.40/40°	14.40/40°
	6.4		4.10/15°	4.90/18°	5.50/20°	6.40/25°	7.90/30°	9.30/35°	10.50/35°	11.50/35°	13.40/35°	15.10/40°	18.40/40°	21.00/40°
	7.0		5.70/15°	6.70/18°	7.50/20°	8.70/25°	10.70/30°	12.40/35°	14.00/35°	15.40/35°	17.90/35°	20.00/40°	24.50/40°	27.80/40°
⅜	7.0		5.70/15°	6.70/18°	7.50/20°	8.70/25°	10.70/30°	12.40/35°	14.00/35°	15.40/35°	17.90/35°	20.00/40°	24.50/40°	27.80/40°
	8.0		7.00/15°	8.40/18°	9.80/20°	11.70/25°	14.10/30°	16.00/35°	17.70/35°	19.50/35°	22.50/35°	25.00/40°	31.00/40°	35.50/40°
	9.0		8.00/15°	10.80/18°	13.00/20°	15.40/25°	18.90/30°	21.70/35°	24.50/35°	26.70/35°	31.70/35°	35.60/40°	43.00/40°	49.00/40°
	11.0		11.50/15°	14.60/18°	16.70/20°	20.10/25°	24.30/30°	28.20/35°	31.20/35°	34.30/35°	38.50/35°	42.40/40°	51.20/40°	58.00/40°
½	9.0		8.00/15°	10.80/18°	13.00/20°	15.40/25°	18.90/30°	21.70/35°	24.50/35°	26.70/35°	31.70/35°	35.60/40°	43.00/40°	49.00/40°
	11.0		11.50/15°	14.60/18°	16.70/20°	20.10/25°	24.30/30°	28.20/35°	31.20/35°	34.30/35°	38.50/35°	42.40/40°	51.20/40°	58.00/40°
	13.5		17.00/15°	23.00/18°	27.00/20°	33.00/25°	41.00/30°	47.00/35°	53.50/35°	58.00/35°	67.00/35°	75.00/40°	93.00/40°	105.00/40°