


K-12

直進タイプ スプレーノズル



管径 in	寸 法 mm		重量 g
	A	B	
1/4	20	10	15
3/8	24	11	30
1/2	32	14	63

※記載の数値は代表値であり、保証値ではありません。

管径 in	吹出穴 mm	水 量 L/min / Spray 角 度													
		水压 (MPa)	0.0196	0.029	0.049	0.069	0.098	0.147	0.196	0.245	0.294	0.392	0.490	0.686	0.980
		(kg/cm ²)	0.2	0.3	0.5	0.7	1.0	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0
1/4	2.0		—	—	1.60/40°	1.90/45°	2.45/50°	3.20/55°	3.60/55°	3.90/55°	4.20/55°	4.63/50°	5.00/50°	6.00/50°	6.50/45°
	2.4			1.60/40°	2.00/45°	2.40/50°	2.90/55°	3.60/55°	4.30/60°	4.90/60°	5.40/60°	6.20/55°	6.90/50°	8.20/50°	9.40/45°
	2.6		1.80/45°	2.20/40°	2.70/55°	3.10/55°	3.65/60°	4.45/60°	5.20/60°	5.90/60°	6.50/60°	7.50/60°	8.40/50°	10.05/50°	11.40/50°
	3.2		2.60/45°	3.00/50°	3.80/55°	4.40/55°	5.20/60°	6.40/60°	7.40/60°	8.20/60°	8.80/60°	10.00/60°	11.00/50°	13.20/50°	14.80/50°
3/8	2.8		2.10/40°	2.70/40°	3.30/45°	3.80/45°	4.50/50°	5.40/50°	6.20/50°	6.80/50°	7.40/50°	8.40/45°	9.25/45°	11.00/45°	12.40/40°
	3.2		3.40/40°	4.00/40°	4.80/50°	5.30/50°	6.20/55°	7.30/55°	8.40/55°	9.30/55°	10.00/55°	11.20/50°	12.30/50°	14.60/46°	16.60/45°
	3.6		4.00/40°	4.60/45°	5.50/50°	6.30/55°	7.60/60°	9.20/60°	10.60/60°	11.80/60°	12.65/60°	14.00/55°	15.30/53°	18.20/50°	21.00/47°
	4.0		4.90/40°	6.00/50°	7.45/55°	8.40/60°	9.80/60°	12.00/65°	13.60/70°	14.60/70°	15.40/70°	17.30/65°	18.80/60°	22.00/55°	24.80/50°
	4.8		6.10/40°	7.30/45°	8.90/60°	10.50/65°	12.90/70°	15.20/80°	17.05/85°	18.50/85°	19.60/85°	21.20/80°	23.00/80°	26.60/70°	29.60/70°
1/2	4.8		7.00/40°	8.20/40°	10.50/45°	12.30/50°	14.40/60°	17.20/65°	19.20/65°	20.80/65°	22.40/65°	25.40/60°	28.00/55°	33.00/50°	37.00/50°
	5.5		7.90/40°	9.10/40°	11.50/45°	13.40/50°	16.30/60°	19.50/65°	21.80/65°	24.00/65°	26.20/65°	29.40/60°	32.40/55°	38.50/50°	44.00/50°
	6.0		8.80/45°	10.20/50°	12.90/60°	15.00/60°	17.90/65°	21.80/70°	24.60/75°	27.00/75°	28.70/75°	32.30/70°	35.90/65°	43.60/60°	50.10/60°
	6.4		9.40/50°	11.40/50°	13.60/60°	15.40/65°	18.50/70°	22.60/80°	25.20/85°	28.30/85°	30.10/85°	34.80/80°	38.40/75°	46.40/70°	53.00/70°