

		No. 図番		A-15302-4T	
予想性能曲線図 PUMP PERFORMANCE CURVES					
TYPE 名 称		汚物用水中ノンクログポンプ		MODEL 型 式	
		TOS50B4.4 -63		FREQUENCY 周波数	
				60 Hz	
CUSTOMER'S NAME 御注文先					
EQUIPMENT TITLE 機器名称					
殿					
No.					
		標 準 仕 様		御 注 文 仕 様	
		STANDARD SPECIFICATIONS		REQUIRED SPECIFICATIONS	
口 径 : DISCHARGE BORE		50 mm		mm	
全揚程 : TOTAL HEAD		4 .5 m		m	
吐出し量 : CAPACITY		0 .21 m³/min		m³/min	
出 力 : MOTOR OUTPUT		0 .4 kW		kW	
相×電圧 : PHASE×VOLTAGE		3 φ × 200 V		φ × V	
電 流 : CURRENT		2 .1 A		A	
極数 : POLES / 回転速度 : SPEED OF ROTATION		4 P / S.S.1800 min ⁻¹		P / min ⁻¹	
始動方式 : STARTING METHOD		じか入始動			
耐熱クラス : INSULATION CLASS		E			
REMARKS:					
The graph plots three performance metrics against capacity (m³/min) on the x-axis (0 to 0.6). The left y-axis has two scales: one for head (m) from 0 to 12, and one for efficiency (%) and output (kW) from 0 to 100. The 'TOTAL HEAD' curve starts at approximately 8.5m at 0 capacity and decreases to about 1.5m at 0.35 m³/min. The 'PUMP EFF.' curve starts at 0, peaks at approximately 45% efficiency at 0.2 m³/min, and then declines. The 'OUTPUT' curve starts at approximately 0.15 kW at 0 capacity and increases to about 0.2 kW at 0.35 m³/min.					
%	kW	m	CAPACITY 吐出し量		
PUMP EFF. ポンプ効率	MOTOR OUTPUT 出力	TOTAL HEAD 全揚程	m³/min		
株式会社 鶴見製作所			TSURUMI MFG. CO., LTD.		