


		No. 図番		A-29782-2T	
予想性能曲線図 PUMP PERFORMANCE CURVES					
TYPE 名 称		汚物用水中ノンクログポンプ		MODEL 型 式	
		TOS80B41.5H -64		FREQUENCY 周波数	
				60 Hz	
CUSTOMER'S NAME 御注文先					
殿					
EQUIPMENT TITLE 機器名称					
No.					
		標 準 仕 様		STANDARD SPECIFICATIONS	
		御 注 文 仕 様		REQUIRED SPECIFICATIONS	
口 径		DISCHARGE BORE		80 mm	
全揚程		TOTAL HEAD		7.5 m	
吐出し量		CAPACITY		0.6 m³/min	
出 力		MOTOR OUTPUT		1.5 kW	
相×電圧		PHASE×VOLTAGE		3 φ × 200 V	
電 流		CURRENT		7.3 A	
極数：POLES		／回転速度：SPEED OF ROTATION		4 P / S.S.1800 min⁻¹	
始動方式		STARTING METHOD		じか入始動	
耐熱クラス		INSULATION CLASS		F	
REMARKS:					
 The graph plots three performance metrics against capacity (m³/min) on the x-axis (0 to 1.2). The left y-axis has two scales: one for head (m) from 0 to 24, and one for efficiency (%) from 10 to 100. The right y-axis has a scale for output (kW) from 0 to 10. The 'TOTAL HEAD' curve starts at approximately 18m at 0 capacity and decreases linearly to about 10m at 0.8 m³/min. The 'PUMP EFF.' curve starts at 0% at 0 capacity, rises to a peak of about 55% at 0.5 m³/min, and then slightly declines. The 'OUTPUT' curve starts at 0 kW at 0 capacity and increases linearly to about 1.5 kW at 0.8 m³/min.					
%	kW	m	CAPACITY		
PUMP EFF.	MOTOR OUTPUT	TOTAL HEAD	吐出し量		
ポンプ効率	出力	全揚程			
株式会社 鶴見製作所			TSURUMI MFG. CO., LTD.		