

		No. 図番		A-26074-3W	
予想性能曲線図 PUMP PERFORMANCE CURVES					
TYPE 名 称		汚物用水中ハイスピンポンプ		MODEL 型 式 40PUW2.15S -55	
				FREQUENCY 周波数 50 Hz	
CUSTOMER'S NAME 御注文先 殿					
EQUIPMENT TITLE 機器名称 No.					
		標 準 仕 様 STANDARD SPECIFICATIONS		御 注 文 仕 様 REQUIRED SPECIFICATIONS	
口 径 : DISCHARGE BORE		40 mm		mm	
全揚程 : TOTAL HEAD		3.8 m		m	
吐出し量 : CAPACITY		0.10 m³/min		m³/min	
出 力 : MOTOR OUTPUT		0.15 kW		kW	
相×電圧 : PHASE×VOLTAGE		1 φ × 100 V		φ × V	
電 流 : CURRENT		4.0 A		A	
極数: POLES / 回転速度: SPEED OF ROTATION		2 P / S.S.3000 min⁻¹		P / min⁻¹	
始動方式 : STARTING METHOD		コンデンサ運転			
耐熱クラス: INSULATION CLASS		E			
The graph plots three performance metrics against Capacity (m³/min) on the x-axis (0 to 0.24). The left y-axis has two scales: one for Head (m) from 0 to 6, and one for Power/Efficiency from 0.1 to 1.0. The 'TOTAL HEAD' curve starts at 6m head at 0 capacity and decreases linearly to 2m head at 0.18 m³/min. The 'PUMP EFF.' curve starts at 0, peaks at approximately 48% efficiency at 0.12 m³/min, and then decreases. The 'OUTPUT' curve starts at approximately 0.12 kW at 0 capacity and increases slightly to about 0.14 kW at 0.18 m³/min.				REMARKS:	
%	kW	m	CAPACITY 吐出し量		
PUMP EFF. ポンプ効率	MOTOR OUTPUT 出力	TOTAL HEAD 全揚程	m³/min		
株式会社 鶴見製作所			TSURUMI MFG. CO., LTD.		