

		No. 図番		A-26063-2	
予想性能曲線図				PUMP PERFORMANCE CURVES	
TYPE 名称		雑排水用水中ハイスピンポンプ		MODEL 型式 32PN(A/W)2.15 -53	
				FREQUENCY 周波数 50 Hz	
CUSTOMER'S NAME 御注文先 殿					
EQUIPMENT TITLE 機器名称 No.					
		標準仕様 STANDARD SPECIFICATIONS		御注文仕様 REQUIRED SPECIFICATIONS	
口 径 : DISCHARGE BORE		32 mm		40 mm	
全揚程 : TOTAL HEAD		5.0/2.0 m			
吐出し量 : CAPACITY		0.08/0.15 m³/min		m³/min	
出 力 : MOTOR OUTPUT		0.15 kW		kW	
相×電圧 : PHASE×VOLTAGE		3 φ × 200 V		φ × V	
電 流 : CURRENT		1.4 A		A	
極数 : POLES / 回転速度 : SPEED OF ROTATION		2 P / S.S.3000 min⁻¹		P / min⁻¹	
始動方式 : STARTING METHOD		じか入始動			
耐熱クラス : INSULATION CLASS		E			
The graph plots three performance metrics against capacity (m³/min). The x-axis ranges from 0 to 0.24 m³/min. The left y-axis has two scales: one for head (m) from 0 to 12, and one for efficiency/output from 0.1 to 1.0. The 'TOTAL HEAD' curve starts at approximately 7.0 m at 0 m³/min and decreases to about 2.0 m at 0.18 m³/min. The 'PUMP EFF.' curve starts at 0, peaks at approximately 0.5 (50%) efficiency at 0.12 m³/min, and then declines. The 'OUTPUT' curve starts at approximately 0.15 kW at 0 m³/min and remains relatively flat, ending at about 0.16 kW at 0.18 m³/min.				REMARKS:	
%	k W	m	CAPACITY 吐出し量		
PUMP EFF. ポンプ 効率	MOTOR OUTPUT 出力	TOTAL HEAD 全揚程			
禁社 鶴見製作所			TSURUMI MFG. CO., LTD.		