

		No. 図番		A-26076-2	
予想性能曲線図				PUMP PERFORMANCE CURVES	
TYPE 名称		汚物用水中ハイスピンポンプ		MODEL 型式 40PU(A/W)2.15 -54	
				FREQUENCY 周波数 50 Hz	
CUSTOMER'S NAME 御注文先 殿					
EQUIPMENT TITLE 機器名称 No.					
		標準仕様 STANDARD SPECIFICATIONS		御注文仕様 REQUIRED SPECIFICATIONS	
口 径 : DISCHARGE BORE		40 mm		50 mm	
全揚程 : TOTAL HEAD		3.8 m		m	
吐出し量 : CAPACITY		0.10 m³/min		m³/min	
出 力 : MOTOR OUTPUT		0.15 kW		kW	
相×電圧 : PHASE×VOLTAGE		3 φ × 200 V		φ × V	
電 流 : CURRENT		1.4 A		A	
極数 : POLES / 回転速度 : SPEED OF ROTATION		2 P / S.S.3000 min⁻¹		P / min⁻¹	
始動方式 : STARTING METHOD		じか入始動			
耐熱クラス : INSULATION CLASS		E			
The graph plots three performance metrics against Capacity (m³/min) on the x-axis (0 to 0.24). The left y-axis has two scales: Head (m) from 0 to 6 and Efficiency (%) from 0 to 100. The right y-axis has a scale for Output (kW) from 0 to 0.3. The 'TOTAL HEAD' curve starts at 6m at 0 capacity and decreases linearly to 2m at 0.17 m³/min. The 'PUMP EFF.' curve starts at 0% at 0 capacity, peaks at approximately 48% efficiency at 0.12 m³/min, and then decreases. The 'OUTPUT' curve starts at approximately 0.12 kW at 0 capacity and increases slightly to about 0.14 kW at 0.17 m³/min.				REMARKS:	
%	kW	m	CAPACITY 吐出し量		
PUMP EFF. ポンプ 効率	MOTOR OUTPUT 出力	TOTAL HEAD 全揚程			
株式会社 鶴見製作所			TSURUMI MFG. CO., LTD.		