


ローノイズケーブル/Low-Noise Cable
LNC-1-XX Assy. 仕様書/Specifications (XX:Cable length m)

- | | |
|---|---|
| 1.外皮材質/ Sheath (色/color) | フッ素樹脂 / Fluororesin (FEP) (黒/Black) |
| 2.外形/ Diameter | Approx. 2.2mm |
| 3.絶縁体/ Dielectric | フッ素樹脂 / Fluororesin (FEP) |
| 4.中心導体/ Central conductor | 銀メッキ銅皮銅線 / Silver plating annealed copper wire
$\phi 0.29 \times 1$ |
| 5.導体抵抗/ Resistance | 約 679 Ω /km 以下 / Less than Approx. 679 Ω /km |
| 6.静電容量/ Capacitance | 75pF/m |
| 7.ノイズ/ Noise | 1pC 以下(1000pF のターミネータを付け 20Hz,10mmp-p で振動)
Less than 1pC(A 1,000pF terminator is attached and it
Vibrates by 20Hz, 10mmp-p) |
| 8.絶縁抵抗/ Insulation resistance | 10,000M Ω 以上 / 10,000M Ω or more (at 20℃) |
| 9.温度範囲/ Temperature range | -250 ~ +200℃ |
| 10.注文方法(型式)/How to order Cable Assembly(Model Name) | |



- a) A: BNC connector B: Miniature connector(10-32UNF) LNC-1A-XX
b) A: Miniature connector(10-32UNF) B: Miniature connector(10-32UNF) LNC-1B-XX
c) A: BNC connector B: BNC connector LNC-1C-XX
XX=ケーブル長さ/Cable Length in "m"

11.外形図/ Outline drawing(mm)

