


RoHS10 Support

○形状 (SHAPE)




○規格 (Standard)
MIL-C-39012

○仕様 (Specification)


特性インピーダンス (Impedance): 50 Ω
 定格周波数 (Working Frequency Range): DC~6GHz
 電圧定在波比 (VSWR): ≤1.30 at 6GHz
 挿入損失 (Insertion Loss): 0.05dB max × √f GHz (f:Frequency)
 定格電圧 (Voltage Rating): 500V rms
 耐電圧 (Proof Voltage): 1000V rms
 接触抵抗 (Contact Resistance): 1mΩ max
 絶縁抵抗 (Insulation Resistance): ≥5000MΩ
 勘合保証回数 (Connector Life): 500 times min
 使用温度範囲 (Temperature range): -40°C~150°C
 推奨締め付けトルク (Recommended Torque): 0.7~1.1Nm

○加工寸法 (ASSEMBLY)


RECOMMENDED CABLE STRIPPING DIMS



SOLDER CONTACT TO CABLE CENTER CONDUCTOR,
BOTTOMING ON INSULATOR



RECOMMENDED CLIPPING TOOL SIZE



RECOMMENDED CRIMP HEIGHT 3.35±0.1

The tolerance in this area is ± 0.10

7	Ring	BRASS	GOLD
6	GASKET	S . I . R	RED
5	R-ring	BRASS	NONE
4	Shell	BRASS	NICKEL
3	Contact	BRASS	GOLD
2	Dielectric	PTFE	NONE
1	Body	BRASS	NICKEL
No	DESCRIPTION	MATERIAL	FINISH



TOLERANCE DECIMALS .XX ±0.10 .X ±0.15 DIAMETER .X ±0.10				日本エレパーツ株式会社 NIHON ELEPARTS Co.,LTD		
Approved	Checked	Drawn				
 エレパーツ '22.03.30 池尾	 エレパーツ '22.03.30 大江	 エレパーツ '22.03.30 山崎	A4	N A M E	N-PS-1.13	REV
						1