




TYPE 名称	清水用渦巻ポンプ	MODEL 型式	TON2-80LW1.5-P	FUREQUENCY 周波数	60 Hz
------------	----------	-------------	----------------	-------------------	-------

予想性能曲線図 PUMP PERFORMANCE CURVES



番号	No.		1	2	3	4	5	6	7	8	9	10
PUMP	吐出量	CAPACITY	m^3/min	0	0.20	0.45	0.70	0.90	1.00	—	—	—
PUMP	全揚程	TOTAL HEAD	m	10.3	10.2	9.5	7.8	5.3	3.6	—	—	—
PUMP	理論動力	WATER POWER	kW	0.00	0.33	0.70	0.89	0.78	0.58	—	—	—
PUMP	ポンプ効率	PUMP EFF.	%	0.0	40.3	59.9	63.1	51.9	38.9	—	—	—
MOTOR	電圧	VOLTAGE	V	200	200	200	200	200	200	—	—	—
MOTOR	電流	CURRENT	A	3.02	3.76	4.77	5.59	5.90	5.89	—	—	—
MOTOR	入力	INPUT	kW	0.58	0.91	1.30	1.58	1.69	1.68	—	—	—
MOTOR	出力	OUTPUT	kW	0.51	0.82	1.17	1.41	1.50	1.49	—	—	—
PUMP	仕様	吐出量CAPACITY	m^3/min				性能	吐出量CAPACITY	m^3/min			
PUMP	REQU.	全揚程TOTAL HEAD	m				PERF. W.	全揚程TOTAL HEAD	m			
PUMP	ポンプ口径	PUMP SIZE	80mm		羽根径	IMP. DIA.	mm		同期回転速度	SYNC. SPEED OF ROTATION	1800 min^{-1}	
MOTOR	型式	MODEL	SF-PR		出力	OUTPUT	1.5kW		相・電圧	PHASE-VOLT.	3φ 200V	
MOTOR	極数・周波数	POLE-FREQ.	4P 60Hz		回転速度	SPEED OF ROTATION	1745 min^{-1}		電流	CURRENT	6A	
MOTOR	製造者	MANUFACT.	MITSUBISHI						電動機CD	MOTOR CD		