




TYPE 名 称	清水用渦巻ポンプ	MODEL 型 式	TON2-100HW7.5-P	FUREQUENCY 周波数	60 Hz
-------------	----------	--------------	-----------------	-------------------	-------

予想性能曲線図 PUMP PERFORMANCE CURVES



番号	No.		1	2	3	4	5	6	7	8	9	10
PUMP	吐出量	CAPACITY	m^3/min	0	0.40	0.71	1.10	1.40	1.60	—	—	—
	全揚程	TOTAL HEAD	m	28.0	28.1	26.7	22.3	16.6	11.4	—	—	—
	理論動力	WATER POWER	kW	0.00	1.83	3.09	4.00	3.79	2.98	—	—	—
	ポンプ効率	PUMP EFF.	%	0.0	41.2	53.3	56.8	50.5	40.0	—	—	—
MOTOR	電圧	VOLTAGE	V	200	200	200	200	200	200	—	—	—
	電流	CURRENT	A	13.4	17.9	21.8	25.9	27.4	27.2	—	—	—
	入力	INPUT	kW	2.84	4.78	6.24	7.66	8.17	8.12	—	—	—
	出力	OUTPUT	kW	2.61	4.45	5.79	7.05	7.50	7.45	—	—	—
PUMP	仕様	吐出量CAPACITY	m^3/min				性能	吐出量CAPACITY	m^3/min			
	REQU.	全揚程TOTAL HEAD	m				PERF. W.	全揚程TOTAL HEAD	m			
	ポンプ口径	PUMP SIZE	100mm		羽根径	IMP. DIA.	mm		同期回転速度	SYNC. SPEED OF ROTATION	1800 min^{-1}	
	型式	MODEL	SF-PR		出力	OUTPUT	7.5kW		相・電圧	PHASE-VOLT.	3φ 200V	
MOTOR	極数・周波数	POLE-FREQ.	4P 60Hz		回転速度	SPEED OF ROTATION	1755 min^{-1}		電流	CURRENT	28A	
	製造者	MANUFACT.	MITSUBISHI						電動機CD	MOTOR CD		