

(単位: mm)

※本製品の設置・転倒
構造耐力上安全な構

固定方法と部材仕様

固定場所	部材 (付属)
木壁固定	木ねじ φ4.8
RC壁固定 ALC壁固定	木ねじ φ4.8 フィッシャ 6×
PS固定	小ねじ M5×

(上方からの透視図)

Diagram showing the top-down perspective view of the unit. Dimensions are provided for various connection points and internal components. Labels include: ポンプ水抜き栓 (Pump water drain plug), ふろ往接続口 (Bath outgoing connection port), 給水接続口 (Water supply connection port), ふろ戻接続口 (Bath return connection port), ガス接続口 (Gas connection port), ドレン配管接続口 (Drainage pipe connection port), 給湯接続口 (Hot water connection port), 中和器水抜き栓 (Neutralizer water drain plug), and ケーブル接続口 (Cable connection port).

接続口	A 寸法
ガス	52
給水	55
給湯	55
ふろ往	40
ふろ戻	40
ケーブル	27
ドレン配管 (オーバーフロー)	44

注

Diagram showing the front view of the unit. Dimensions include: 610 (total height), 580 (height to top of unit), 15 (top flange thickness), 250 (top width), 224 (bottom width), 608 (height to bottom of unit), and 267 (bottom width). Labels include: 取付金具上 (Top mounting bracket) and 取付金具下 (Bottom mounting bracket).

Diagram showing the side view of the unit. Dimensions include: 310 (total width), 267 (width to side of unit), 10 (side flange thickness), 163 (width to center of unit), 580 (height to top of unit), 654 (height to bottom of unit), and 267 (bottom width).

Diagram showing a detail view of the unit's connection points and mounting brackets. Dimensions include: 37 (height to top of unit), 24.5 (height to center of unit), 580 (height to bottom of unit), and 37 (height to bottom of unit).

壁掛