



748 (屋内ケース取付ピッチ)

100
70
40
2×6.5×10長穴
1.2
12
12
17
8.5°
10
12
18

748 (屋内ケース取付ピッチ)

7×12.5長穴
23
9

748
(扉内ケース取付ピッチ)

7x12.5長穴

23

9

適応金棒	標準設置形Ⅱ型
参考図面	(図番 W-00-0337)

Technical drawing of the NPB-1000 unit, showing front and top views with dimensions and labels.

Top View Dimensions:

- Overall width: 474
- Mounting bracket width: 480
- Base width: 460

Front View Dimensions and Labels:

- Overall height: 740
- Mounting bracket height: 706
- Top panel height: 25
- Top panel width: 84
- Exhaust port (排气口) diameter: 240
- Exhaust port label: A部
- Filter (フィルタ) label: B部
- Electrical wiring cover (電気配線用扉) label: C部
- Bottom panel height: 17
- Bottom panel width: 454
- Bottom panel label: (扉内ケース取付ピッチ)

※ 1: 電源コードが無い機種もあります。
 ※ 2: ガス消費量、出流量、給湯能力はガス種13Aの値です。ガス種により若干異なります。
 ※ 3: 各特性値及び付属部品、別売品は予告なく変更する事が有ります。

■注記

※ 標準塗装は(一社)日本冷凍空調工業会標準規格(JRA9002)の前庭書仕様にて準拠しています。
 ※ この機器は前面直径10mmに対応しています。
 ※ この機器は燃焼時にドレン排水口からドレンが排出されます。必ず排水配管を設置し、排水口で配管した場合は大気開放して、水に付かないようにしてください。
 ※ 壁掛け設置、PS標準設置の超超薄層設置(高さ:30m/s以下)に対応可能です。
 ※ 排水延長は、1~4曲が7m以内で施工します。(排水間隔径:φ80)

納入仕様図	製品名		GTH-C1670SAW-TBL (潜熱回収型) FT2825ARS4SCM				
	図名		名称寸法図				
	尺度	1/10	原紙サイズ	A3	図番	WN-25-0065	
	作成	2025. 9. 1	調整	-	-	株式会社ノリツ	