


ベアリングテクノロジー | すべり軸受 | イグリュールG

スリーブ型ベアリング (形状S)



²⁾ 肉厚 < 0.6mm、面取り=20°

内径d1を面取り加工

d1 [mm]	∅ 1-6	∅ 6-12	∅ 12-30	∅ > 30
f1 [mm]	0.3	0.5	0.8	1.2

ISO 3547-1に準拠した寸法および特殊寸法

注文例 **GSM-0103-02** - 最小注文数量なし
Gイグリュール材質 Sスリーブ型 Mメートル寸法 02内径d1 03外径d2 03全長b1

d1	d1 公差 ³⁾	d2	b1 h13	製品番号	d1	d1 公差 ³⁾	d2	b1 h13	製品番号
[mm]		[mm]	[mm]		[mm]		[mm]	[mm]	
1.5		3.0	2.0	GSM-0103-02	6.0		8.0	8.0	GSM-0608-08
2.0		3.5	3.0	GSM-0203-03	6.0	+0.020	8.0	9.5	GSM-0608-09
2.5	+0.014	4.5	5.0	GSM-02504-05	6.0	+0.068	8.0	10.0	GSM-0608-10
3.0	+0.054	4.5	3.0	GSM-0304-03	6.0		8.0	11.8	GSM-0608-11
3.0		4.5	5.0	GSM-0304-05	6.0		8.0	13.8	GSM-0608-13
3.0		4.5	6.0	GSM-0304-06	7.0	+0.013	8.0	10.0	GSM-0708-10
4.0		5.5	4.0	GSM-0405-04	7.0	+0.049	8.0	19.0	GSM-0708-19
4.0	+0.020	5.5	6.0	GSM-0405-06	7.0		9.0	8.0	GSM-0709-08
4.0	+0.068	7.0	5.5	GSM-0407-05	7.0	+0.025	9.0	9.0	GSM-0709-09
4.5		6.0	8.0	GSM-0406-08	7.0	+0.083	9.0	10.0	GSM-0709-10
5.0		6.0	4.6	GSM-0506-046	7.0		9.0	12.0	GSM-0709-12
5.0	+0.010	6.0	5.0	GSM-0506-05	8.0		9.0	5.0	GSM-0809-05
5.0	+0.040	6.0	7.0	GSM-0506-07	8.0	+0.013	9.0	6.0	GSM-0809-06
5.0		7.0	5.0	GSM-0507-05	8.0	+0.049	9.0	8.0	GSM-0809-08
5.0	+0.020	7.0	7.0	GSM-0507-07	8.0		9.0	12.0	GSM-0809-12
5.0	+0.068	7.0	8.0	GSM-0507-08	8.0		10.0	5.0	GSM-0810-05
5.0		7.0	10.0	GSM-0507-10	8.0		10.0	6.0	GSM-0810-06
6.0		7.0	6.0	GSM-0607-06	8.0		10.0	6.8	GSM-0810-07
6.0		7.0	12.0	GSM-0607-12	8.0		10.0	8.0	GSM-0810-08
6.0	+0.010	7.0	17.0	GSM-0607-17	8.0		10.0	10.0	GSM-0810-10
6.0	+0.040	7.0	17.5	GSM-0607-17.5	8.0		10.0	12.0	GSM-0810-12
6.0		7.0	19.0	GSM-0607-19	8.0	+0.025	10.0	13.8	GSM-0810-13
6.0		8.0	1.5	GSM-0608-015	8.0	+0.083	10.0	14.0	GSM-0810-14
6.0		8.0	2.5	GSM-0608-025	8.0		10.0	15.0	GSM-0810-15
6.0		8.0	3.0	GSM-0608-03	8.0		10.0	16.0	GSM-0810-16
6.0	+0.020	8.0	4.0	GSM-0608-04	8.0		10.0	18.0	GSM-0810-18
6.0	+0.068	8.0	5.0	GSM-0608-05	8.0		10.0	20.0	GSM-0810-20
6.0		8.0	5.5	GSM-0608-055	8.0		10.0	22.0	GSM-0810-22
6.0		8.0	6.0	GSM-0608-06	8.0		10.0	25.0	GSM-0810-25

³⁾ 圧入後、試験方法、61ページ

製品概要

d1	d1 公差 ³⁾	d2	b1 h13	製品番号	d1	d1 公差 ³⁾	d2	b1 h13	製品番号
[mm]		[mm]	[mm]		[mm]		[mm]	[mm]	
8.0	+0.040	12.0	9.0	GSM-0812-09	13.0		15.0	7.0	GSM-1315-070
	+0.130				13.0		15.0	7.5	GSM-1315-075
9.0	+0.013	10.0	12.0	GSM-0910-12	13.0		15.0	10.0	GSM-1315-10
9.0	+0.049	10.0	16.0	GSM-0910-16	13.0		15.0	15.0	GSM-1315-15
9.0	+0.025	11.0	6.0	GSM-0911-06	13.0		15.0	20.0	GSM-1315-20
9.0	+0.083	11.0	20.0	GSM-0911-20	13.0		15.0	25.0	GSM-1315-25
10.0		11.0	6.0	GSM-1011-06	14.0		16.0	3.0	GSM-1416-03
10.0		11.0	7.0	GSM-1011-07	14.0	+0.032	16.0	6.0	GSM-1416-06
10.0	+0.013	11.0	10.0	GSM-1011-10	14.0	+0.102	16.0	8.0	GSM-1416-08
10.0	+0.049	11.0	20.0	GSM-1011-20	14.0		16.0	10.0	GSM-1416-10
10.0		11.0	25.0	GSM-1011-25	14.0		16.0	12.0	GSM-1416-12
10.0		11.0	30.0	GSM-1011-30	14.0		16.0	15.0	GSM-1416-15
10.0		12.0	4.0	GSM-1012-04	14.0		16.0	20.0	GSM-1416-20
10.0		12.0	4.5	GSM-1012-045	14.0		16.0	25.0	GSM-1416-25
10.0		12.0	5.0	GSM-1012-05	14.0		16.0	45.0	GSM-1416-45
10.0		12.0	6.0	GSM-1012-06	15.0	+0.016	16.0	10.0	GSM-1516-10
10.0		12.0	7.0	GSM-1012-07	15.0	+0.059	16.0	15.0	GSM-1516-15
10.0		12.0	8.0	GSM-1012-08	15.0		17.0	4.0	GSM-1517-04
10.0	+0.025	12.0	9.0	GSM-1012-09	15.0		17.0	10.0	GSM-1517-10
10.0	+0.083	12.0	10.0	GSM-1012-10	15.0		17.0	12.0	GSM-1517-12
10.0		12.0	12.0	GSM-1012-12	15.0		17.0	15.0	GSM-1517-15
10.0		12.0	14.0	GSM-1012-14	15.0		17.0	20.0	GSM-1517-20
10.0		12.0	15.0	GSM-1012-15	15.0		17.0	25.0	GSM-1517-25
10.0		12.0	17.0	GSM-1012-17	16.0		18.0	5.5	GSM-1618-055
10.0		12.0	20.0	GSM-1012-20	16.0		18.0	8.0	GSM-1618-08
10.0		13.0	13.5	GSM-1013-13	16.0	+0.032	18.0	10.0	GSM-1618-10
10.0	+0.025	14.0	10.0	GSM-1014-10	16.0	+0.102	18.0	12.0	GSM-1618-12
10.0	+0.115	14.0	20.0	GSM-1014-20	16.0		18.0	13.5	GSM-1618-13.5
10.0	+0.040				16.0		18.0	15.0	GSM-1618-15
10.0	+0.130	16.0	10.0	GSM-1016-10	16.0		18.0	20.0	GSM-1618-20
					16.0		18.0	25.0	GSM-1618-25
12.0		13.0	4.7	GSM-1213-047	16.0		18.0	30.0	GSM-1618-30
12.0	+0.016	13.0	10.0	GSM-1213-10	16.0		18.0	38.5	GSM-1618-38.5
12.0	+0.059	13.0	12.0	GSM-1213-12	16.0		18.0	50.0	GSM-1618-50
12.0		13.0	15.0	GSM-1213-15	16.0		18.0	50.0	GSM-1618-50
12.0		14.0	4.0	GSM-1214-04	17.0		19.0	15.0	GSM-1719-15
12.0		14.0	5.0	GSM-1214-05		+0.016			
12.0		14.0	6.0	GSM-1214-06		+0.059	19.0	15.0	GSM-1819-15
12.0		14.0	8.0	GSM-1214-08	18.0		20.0	6.0	GSM-1820-06
12.0		14.0	10.0	GSM-1214-10	18.0		20.0	10.0	GSM-1820-10
12.0	+0.032	14.0	12.0	GSM-1214-12	18.0		20.0	12.0	GSM-1820-12
12.0	+0.102	14.0	14.0	GSM-1214-14	18.0		20.0	15.0	GSM-1820-15
12.0		14.0	15.0	GSM-1214-15	18.0	+0.032	20.0	20.0	GSM-1820-20
12.0		14.0	20.0	GSM-1214-20	18.0	+0.102	20.0	25.0	GSM-1820-25
12.0		14.0	25.0	GSM-1214-25	18.0		20.0	34.0	GSM-1820-34
12.0		15.0	6.0	GSM-1215-06	18.0		20.0	38.0	GSM-1820-38
12.0		15.0	22.0	GSM-1215-22	18.0		20.0	45.0	GSM-1820-45
12.0	+0.050	16.0	10.0	GSM-1216-10	18.0		22.0	30.0	GSM-1822-30
12.0	+0.160	16.0	20.0	GSM-1216-20					

³⁾ 圧入後、試験方法、61ページ

ベアリングテクノロジー | すべり軸受 | イグリデュールG

d1	d1 公差 ³⁾	d2	b1 h13	製品番号	d1	d1 公差 ³⁾	d2	b1 h13	製品番号
[mm]		[mm]	[mm]		[mm]		[mm]	[mm]	
19.0		22.0	6.0	GSM-1922-06	25.0		28.0	24.0	GSM-2528-24
19.0	+0.040	22.0	28.0	GSM-1922-28	25.0		28.0	25.0	GSM-2528-25
19.0	+0.124	22.0	35.0	GSM-1922-35	25.0		28.0	30.0	GSM-2528-30
20.0	+0.020	21.0	20.0	GSM-2021-20	25.0		28.0	35.0	GSM-2528-35
20.0	+0.072	22.0	3.0	GSM-2022-03	25.0		28.0	50.0	GSM-2528-50
20.0		22.0	8.0	GSM-2022-08	26.0		30.0	16.0	GSM-2630-16
20.0		22.0	10.5	GSM-2022-105	27.0	+0.040	30.0	5.0	GSM-2730-05
20.0		22.0	15.0	GSM-2022-15	28.0	+0.124	32.0	10.5	GSM-2832-105
20.0		22.0	20.0	GSM-2022-20	28.0		32.0	12.0	GSM-2832-12
20.0		22.0	22.0	GSM-2022-22	28.0		32.0	15.0	GSM-2832-15
20.0		22.0	28.0	GSM-2022-28	28.0		32.0	20.0	GSM-2832-20
20.0		22.0	30.0	GSM-2022-30	28.0		32.0	23.0	GSM-2832-23
20.0		22.0	47.0	GSM-2022-47	28.0		32.0	25.0	GSM-2832-25
20.0		23.0	4.5	GSM-2023-045	28.0		32.0	30.0	GSM-2832-30
20.0		23.0	10.0	GSM-2023-10	28.0	+0.065	35.0	19.0	GSM-2835-19
20.0		23.0	15.0	GSM-2023-15	28.0	+0.195	35.0	28.0	GSM-2835-28
20.0		23.0	20.0	GSM-2023-20	29.0	+0.040	33.0	6.0	GSM-2933-06
20.0		23.0	24.0	GSM-2023-24	29.0	+0.124	33.0	6.0	GSM-2933-06
20.0	+0.040	23.0	25.0	GSM-2023-25	30.0	+0.020	31.0	5.0	GSM-3031-05
20.0	+0.124	23.0	30.0	GSM-2023-30	30.0	+0.072	31.0	12.0	GSM-3031-12
20.0		23.0	35.0	GSM-2023-35	30.0		31.0	30.0	GSM-3031-30
22.0		24.0	8.0	GSM-2224-08	30.0		34.0	12.0	GSM-3034-12
22.0		24.0	10.0	GSM-2224-10	30.0		34.0	15.0	GSM-3034-15
22.0		24.0	12.0	GSM-2224-12	30.0		34.0	20.0	GSM-3034-20
22.0		24.0	15.0	GSM-2224-15	30.0	+0.040	34.0	24.0	GSM-3034-24
22.0		24.0	17.0	GSM-2224-17	30.0	+0.124	34.0	25.0	GSM-3034-25
22.0		24.0	20.0	GSM-2224-20	30.0		34.0	30.0	GSM-3034-30
22.0		24.0	20.0	GSM-2224-20	30.0		34.0	35.0	GSM-3034-35
22.0		24.0	30.0	GSM-2224-30	30.0		34.0	40.0	GSM-3034-40
22.0		24.0	48.0	GSM-2224-48	30.0		34.0	52.5	GSM-3034-525
22.0		25.0	15.0	GSM-2225-15	32.0		36.0	15.0	GSM-3236-15
22.0		25.0	20.0	GSM-2225-20	32.0		36.0	20.0	GSM-3236-20
22.0		25.0	25.0	GSM-2225-25	32.0		36.0	30.0	GSM-3236-30
22.0		25.0	30.0	GSM-2225-30	32.0		36.0	40.0	GSM-3236-40
22.0		25.0	38.5	GSM-2225-38.5	32.0		36.0	40.0	GSM-3236-40
24.0	+0.020	25.0	25.0	GSM-2425-25	35.0		39.0	14.0	GSM-3539-14
24.0	+0.072	27.0	6.0	GSM-2427-06	35.0		39.0	20.0	GSM-3539-20
24.0		27.0	15.0	GSM-2427-15	35.0		39.0	25.0	GSM-3539-25
24.0	+0.040	27.0	20.0	GSM-2427-20	35.0	+0.050	39.0	30.0	GSM-3539-30
24.0	+0.124	27.0	24.0	GSM-2427-24	35.0	+0.150	39.0	40.0	GSM-3539-40
24.0		27.0	25.0	GSM-2427-25	35.0		39.0	50.0	GSM-3539-50
24.0		27.0	30.0	GSM-2427-30	36.0		40.0	20.0	GSM-3640-20
25.0	+0.020	26.0	23.0	GSM-2526-23	37.0		41.0	20.0	GSM-3741-20
25.0	+0.072	26.0	25.0	GSM-2526-25	38.0		42.0	25.0	GSM-3842-25
25.0		28.0	12.0	GSM-2528-12	40.0		44.0	10.0	GSM-4044-10
25.0	+0.040	28.0	15.0	GSM-2528-15	40.0		44.0	16.5	GSM-4044-16
25.0	+0.124	28.0	20.0	GSM-2528-20	40.0		44.0	20.0	GSM-4044-20
25.0		28.0	20.0	GSM-2528-20	40.0		44.0	30.0	GSM-4044-30

³⁾ 圧入後、試験方法、61ページ


製品概要

d1	d1 公差 ³⁾	d2	b1 h13	製品番号	d1	d1 公差 ³⁾	d2	b1 h13	製品番号
[mm]		[mm]	[mm]		[mm]		[mm]	[mm]	
40.0		44.0	40.0	GSM-4044-40	62.0	+0.100	67.0	35.0	GSM-6267-35
40.0		44.0	50.0	GSM-4044-50	62.0	+0.250	67.0	72.0	GSM-6267-72
40.0		44.0	52.5	GSM-4044-525	62.0		67.0	30.0	GSM-6570-30
42.0		46.0	40.0	GSM-4246-40	65.0		70.0	30.0	GSM-6570-30
44.0		48.0	20.0	GSM-4448-20	65.0		70.0	50.0	GSM-6570-50
45.0		50.0	10.0	GSM-4550-10	65.0		70.0	104.0	GSM-6570-104
45.0		50.0	20.0	GSM-4550-20	68.0		73.0	60.0	GSM-6873-60
45.0		50.0	22.0	GSM-4550-22	70.0	+0.060	75.0	60.0	GSM-7075-60
45.0		50.0	23.5	GSM-4550-235	72.0	+0.180	77.0	24.5	GSM-7277-24.5
45.0	+0.050	50.0	30.0	GSM-4550-30	72.0		77.0	76.0	GSM-7277-76
45.0	+0.150	50.0	38.0	GSM-4550-38	75.0		80.0	40.0	GSM-7580-40
45.0		50.0	40.0	GSM-4550-40	75.0		80.0	60.0	GSM-7580-60
45.0		50.0	50.0	GSM-4550-50	80.0		85.0	60.0	GSM-8085-60
50.0		55.0	20.0	GSM-5055-20	80.0		85.0	100.0	GSM-8085-100
50.0		55.0	25.0	GSM-5055-25	85.0		90.0	100.0	GSM-8590-100
50.0		55.0	30.0	GSM-5055-30	90.0		95.0	100.0	GSM-9095-100
50.0		55.0	40.0	GSM-5055-40	95.0		100.0	100.0	GSM-95100-100
50.0		55.0	50.0	GSM-5055-50	100.0		105.0	21.5	GSM-100105-21.5
50.0		55.0	60.0	GSM-5055-60	100.0	+0.072	105.0	30.0	GSM-100105-30
52.0		57.0	20.0	GSM-5257-20	100.0	+0.212	105.0	32.0	GSM-100105-32
55.0		60.0	20.0	GSM-5560-20	100.0		105.0	100.0	GSM-100105-100
55.0		60.0	40.0	GSM-5560-40	105.0		110.0	100.0	GSM-105110-100
55.0		60.0	50.0	GSM-5560-50	110.0		115.0	100.0	GSM-110115-100
55.0	+0.060	60.0	60.0	GSM-5560-60	120.0		125.0	100.0	GSM-120125-100
60.0	+0.180	65.0	30.0	GSM-6065-30	125.0		130.0	100.0	GSM-125130-100
60.0		65.0	40.0	GSM-6065-40	130.0		135.0	100.0	GSM-130135-100
60.0		65.0	50.0	GSM-6065-50	135.0	+0.085	140.0	80.0	GSM-135140-80
60.0		65.0	60.0	GSM-6065-60	140.0	+0.245	145.0	100.0	GSM-140145-100
60.0		65.0	70.0	GSM-6065-70	140.0		145.0	104.0	GSM-140145-104
60.0		65.0	70.0	GSM-6065-70	150.0		155.0	100.0	GSM-150155-100

³⁾ 圧入後、試験方法、61ページ

 在庫から入手可能
納期は、オンラインで確認ください
www.igus.co.jp/24

 オンライン注文
納期、価格、オンラインツールを含む
www.igus.co.jp/G

 発注書
当社の価格は注文数に応じて変動します。
現在の価格はオンラインでご確認いただけます。

最少注文金額なし
小口注文による追加料金なし