


ベアリングテクノロジー | すべり軸受 | イグリデュールX

フランジ型ベアリング(形状F)



²⁾ 肉厚 < 0.6mm、面取り=20°

内径d1を面取り加工

d1 [mm]	Ø 1-6	Ø 6-12	Ø 12-30	Ø > 30
f1 [mm]	0.3	0.5	0.8	1.2

ISO 3547-1に準拠した寸法および特殊寸法

注文例 **XFM-0304-05** - 最小注文数量なし
Xイグリデュール材質 Fフランジ型 Mメートル寸法 03内径d1 04外径d2 05全長b1

d1	d1	d2	d3	b1	b2	製品番号
[mm]	公差 ³⁾	[mm]	d13 ³⁾	h13	h13	
2.0	+0.006	4.0	6.0	3.0	1.00	XFM-020406-03
3.0	+0.046	4.5	7.5	5.0	0.75	XFM-0304-05
4.0		5.5	9.5	4.0	0.75	XFM-0405-04
4.0		5.5	9.5	6.0	0.75	XFM-0405-06
4.0	+0.010	5.5	8.0	6.0	0.75	XFM-040508-06
5.0	+0.058	7.0	11.0	5.0	1.00	XFM-0507-05
6.0		8.0	12.0	4.0	1.00	XFM-0608-04
6.0		8.0	12.0	8.0	1.00	XFM-0608-08
6.0		8.0	12.0	10.0	1.00	XFM-0608-10
8.0		10.0	12.0	4.0	1.00	XFM-081012-04
8.0		10.0	15.0	5.5	1.00	XFM-0810-05
8.0		10.0	15.0	7.5	1.00	XFM-0810-07
8.0		10.0	15.0	8.0	1.00	XFM-0810-08
8.0		10.0	15.0	9.5	1.00	XFM-0810-09
8.0		10.0	14.0	31.5	1.00	XFM-081014-31
9.0		11.0	15.0	18.0	1.00	XFM-0911-18
10.0		12.0	18.0	5.0	1.00	XFM-1012-05
10.0	+0.013	12.0	18.0	6.0	1.00	XFM-1012-06
10.0	+0.071	12.0	18.0	7.0	1.00	XFM-1012-07
10.0		12.0	15.0	8.0	1.00	XFM-1012-08
10.0		12.0	18.0	9.0	1.00	XFM-1012-09
10.0		12.0	18.0	12.0	1.00	XFM-1012-12
10.0		12.0	18.0	15.0	1.00	XFM-1012-15
10.0		12.0	18.0	17.0	1.00	XFM-1012-17
10.0		12.0	18.0	18.0	1.00	XFM-1012-18
10.0		12.0	15.0	22.0	1.00	XFM-1012-22
10.0		12.0	18.0	25.0	1.00	XFM-1012-25

d1	d1	d2	d3	b1	b2	製品番号
[mm]	公差 ³⁾	[mm]	d13 ³⁾	h13	h13	
12.0		14.0	18.0	3.9	1.00	XFM-121418-039
12.0		14.0	20.0	5.5	1.00	XFM-1214-055
12.0		14.0	18.0	5.9	1.00	XFM-121418-059
12.0		14.0	20.0	9.0	1.00	XFM-1214-09
12.0		14.0	20.0	12.0	1.00	XFM-1214-12
12.0		14.0	20.0	15.0	1.00	XFM-1214-15
12.0		14.0	20.0	17.0	1.00	XFM-1214-17
14.0		16.0	22.0	10.0	1.00	XFM-1416-10
14.0		16.0	22.0	12.0	1.00	XFM-1416-12
14.0	+0.016	16.0	22.0	17.0	1.00	XFM-1416-17
15.0	+0.086	17.0	23.0	6.0	1.00	XFM-1517-06
15.0		17.0	23.0	9.0	1.00	XFM-1517-09
15.0		17.0	23.0	12.0	1.00	XFM-1517-12
15.0		17.0	23.0	17.0	1.00	XFM-1517-17
16.0		18.0	24.0	12.0	1.00	XFM-1618-12
16.0		18.0	24.0	17.0	1.00	XFM-1618-17
18.0		20.0	26.0	12.0	1.00	XFM-1820-12
18.0		20.0	26.0	17.0	1.00	XFM-1820-17
18.0		20.0	26.0	22.0	1.00	XFM-1820-22
20.0		23.0	30.0	6.5	1.50	XFM-2023-065
20.0		23.0	30.0	7.5	1.50	XFM-2023-075
20.0		23.0	30.0	11.5	1.50	XFM-2023-11
20.0		23.0	30.0	16.5	1.50	XFM-2023-16
20.0	+0.020	23.0	30.0	21.0	1.50	XFM-2023-21
25.0	+0.104	28.0	33.0	8.0	1.00	XFM-252833-08
25.0		28.0	35.0	11.5	1.50	XFM-2528-11
25.0		28.0	35.0	13.5	1.50	XFM-2528-13
25.0		28.0	35.0	16.5	1.50	XFM-2528-16

³⁾ 圧入後、試験方法 61ページ

製品概要

d1	d1	d2	d3	b1	b2	製品番号
[mm]	公差 ³⁾	[mm]	d13 ³⁾	h13	h13	
25.0		28.0	35.0	21.0	1.50	XFM-2528-21
27.0		30.0	38.0	20.0	1.50	XFM-2730-20
30.0	+0.020	34.0	42.0	16.0	2.00	XFM-3034-16
30.0	+0.104	34.0	42.0	26.0	2.00	XFM-3034-26
30.0		34.0	42.0	40.0	2.00	XFM-3034-40
32.0		36.0	45.0	15.0	2.00	XFM-3236-15
32.0	+0.025	36.0	45.0	26.0	2.00	XFM-3236-26
35.0	+0.125	39.0	47.0	16.0	2.00	XFM-3539-16
35.0		39.0	47.0	26.0	2.00	XFM-3539-26

³⁾ 圧入後、試験方法 61ページ

d1	d1	d2	d3	b1	b2	製品番号
[mm]	公差 ³⁾	[mm]	d13 ³⁾	h13	h13	
40.0		44.0	52.0	22.0	2.00	XFM-4044-22
40.0	+0.025	44.0	52.0	30.0	2.00	XFM-4044-30
40.0	+0.125	44.0	52.0	40.0	2.00	XFM-4044-40
45.0		50.0	58.0	50.0	2.00	XFM-4550-50
50.0		55.0	63.0	40.0	2.00	XFM-5055-40
60.0	+0.030	65.0	73.0	40.0	2.00	XFM-6065-40
70.0	+0.150	75.0	83.0	40.0	2.00	XFM-7075-40
75.0		80.0	88.0	50.0	2.00	XFM-7580-50

在庫から入手可能
納期は、オンラインで確認ください
www.igus.co.jp/24

オンライン注文
納期、価格、オンラインツールを含む
www.igus.co.jp/X

発注書
当社の価格は注文数に応じて変動します。
現在の価格はオンラインでご確認いただけます。

最少注文金額なし
小口注文による追加料金なし