

寸法単位:mm

サイズ	TS					HITS					D	d	ねじ部 基準径の外径 D1	ねじ山数 (25.4mmにつき)	ねじ部 基準径の位置a	有効ねじ部の 長さL1 (最小)	L2 (最小)	W (最小)	L	B (最小)
	コード	価格	梱包	DXF	納入製品図	コード	価格	梱包	DXF	納入製品図										
◎ 13	5 222270 -	1,130	120 (20×6)	DL	DL	5 225270 -	1,710	120 (20×6)	DL	DL	24	13	20.955	14	8.16±1.81	13.16	4	6	60+5/-2	27
◎ 16	5 222271 -	1,170	80 (20×4)	DL	DL	5 225271 -	1,920	80 (20×4)	DL	DL	29	13	20.955	14	8.16±1.81	13.16	4	6	65+5/-2	32
◎ 20	5 222272 -	1,650	48 (12×4)	DL	DL	5 225272 -	2,450	48 (12×4)	DL	DL	33	19	26.441	14	9.53±1.81	14.53	5	8	75+5/-2	35
20×13	-	-	-	-	-	5 225294 -	2,230	80 (20×4)	DL	DL	33	13	20.955	14	8.16±1.81	13.16	4	6	75+5/-2	34
◎ 25	5 222273 -	2,480	32 (8×4)	DL	DL	5 225273 -	3,630	32 (8×4)	DL	DL	40	25	33.249	11	10.39±2.31	16.79	5	8	85+5/-2	47
◎ 30	5 222274 -	3,630	26	DL	DL	5 225274 -	4,930	26	DL	DL	46	33	41.91	11	12.70±2.31	19.1	5	10	95+5/-2	55
◎ 40	5 222275 -	4,430	26	DL	DL	5 225275 -	5,920	26	DL	DL	57	39	47.803	11	12.70±2.31	19.1	5	10	110+5/-2	65
◎ 50	5 222276 -	6,340	16	DL	DL	5 225276 -	7,700	16	DL	DL	70	50	59.614	11	15.88±2.31	23.38	5	12	125+5/-2	75
65	5 222287 -	15,350	10	DL	DL	5 225327 -	17,580	10	DL	DL	87	66.3	75.184	11	17.46±3.46	26.66	5.5	14	133+5/-2	90
75	5 222288 -	19,830	6	DL	DL	5 225328 -	22,860	6	DL	DL	102	79.5	87.884	11	20.64±3.46	29.84	5	16	145+5/-2	115
100	5 222289 -	29,410	4	DL	DL	5 225329 -	33,880	4	DL	DL	130	103.1	113.03	11	25.40±3.46	35.8	5	18	186+5/-2	140

●金属おねじ部の材質は、JIS H 5121の青銅とする。

●ねじ部は、JIS B 0203のテーパおねじに準ずる。

◎ : JIS規格対象品

65~100

