


54・SSA-G550

ハリマーク・警告ラベル

※～2011年1月
5/5A

給油一覧表





























No	給油項目	使用オイル	容量	換油間隔 (時間)	換油回数 (100時間あたり)
1	燃料	軽油 (JIS規格)	20L	—	—
2	エンジンオイル	SAE10W-30	5L (1.32gal)	50	2
3	エンジンオイル	SAE10W-30	5L	100	1
4	サンプンオイル	SAE10W-30	1.0L	50	2
5	フロントダンパー	SAE10W-30	0.6L	100	1
6	後部ダンパー	SAE10W-30	0.6L	100	1
7	後部ダンパー	SAE10W-30	0.6L	100	1
8	エンジンオイル	SAE10W-30	5L	50	2
9	エンジンオイル	SAE10W-30	5L	100	1
10	エンジンオイル	SAE10W-30	5L	100	1
11	エンジンオイル	SAE10W-30	5L	100	1
12	エンジンオイル	SAE10W-30	5L	100	1

走行速度

ギア	1	2	3	4	5
前進	1.5	2.0	2.4	2.8	3.2
後進	1.5	2.0	2.4	2.8	3.2

この車両に使用されている金油圧式
パワーステアリング用高圧ホースは
2年毎に交換して下さい。

前進する時は、主変速レバーを
(F) 側に倒してから所望の
変速位置に合わせてください。



※2011年2月～

15A 噴霧用ポンプ ON/OFF

44 タコメータ

43 希釈倍率早見表

希釈倍率	400L	500L	600L	700L	800L	900L	1000L
200倍	2000	2500	3000	3500	4000	4500	5000
300倍	1333	1667	2000	2333	2667	3000	3333
400倍	1000	1250	1500	1750	2000	2250	2500
500倍	800	1000	1200	1400	1600	1800	2000
600倍	667	833	1000	1167	1333	1500	1667
700倍	571	714	857	1000	1143	1286	1429
800倍	500	625	750	875	1000	1125	1250
900倍	444	556	667	778	889	1000	1111
1000倍	400	500	600	700	800	900	1000
1200倍	333	417	500	583	667	750	833
1400倍	286	357	429	500	571	643	714
1600倍	250	313	375	438	500	562	625
1800倍	222	278	333	389	444	500	556
2000倍	200	250	300	350	400	450	500

投入薬剤量 (g)