



補償導線：シリコン被覆又はガラスウール+SUS シールド被覆

型 式	種類	D : φ mm	L : mm	シース材質	常用限度 : °C
YS-1-K-0510	K	0.5	100	SUS 316	600
YS-1-K-0515			150		
YS-1-K-0520			200		
YS-1-K-0525			250		
YS-1-K-0530			300		
YS-1-K-1010	K	1.0	100	SUS 316	650
YS-1-K-1015			150		
YS-1-K-1020			200		
YS-1-K-1025			250		
YS-1-K-1030	K	1.6	300	SUS 316	650
YS-1-K-1610			100		
YS-1-K-1615			150		
YS-1-K-1620			200		
YS-1-K-1625			250		
YS-1-K-1630			300		
YS-1-K-2310	K	2.3	100	SUS 316	650
YS-1-K-2315			150		
YS-1-K-2320			200		
YS-1-K-2325			250		
YS-1-K-2330			300		

型 式	種類	D : φ mm	L : mm	シース材質	常用限度 : °C
YS-1-K-3210	K	3.2	100	SUS 316	750
YS-1-K-3220			200		
YS-1-K-3225			250		
YS-1-K-3230			300		
YS-1-K-3250			500		
YS-1-K-4810	K	4.8	100	SUS 316	800
YS-1-K-4820			200		
YS-1-K-4825			250		
YS-1-K-4830			300		
YS-1-K-4850	K	6.4	500	SUS 316	800
YS-1-K-6410			100		
YS-1-K-6420			200		
YS-1-K-6425			250		
YS-1-K-6430			300		
YS-1-K-6450	K	8.0	500	SUS 316	900
YS-1-K-8010			100		
YS-1-K-8020			200		
YS-1-K-8025			250		
YS-1-K-8030			300		
YS-1-K-8050			500		

△					DRAWN	APPROVAL	TITLE	熱電対 YS-1	
△					DESIGN	T. M	SPEC. NO	SCALE	DWG. NO
△					CHECKED	S. K	DATE	N. T. S / mm	YC300-025
△	DATE	PREP'D	APP'D	REASON	REVISION		2004. 7. 26	 株式会社 ヤガミ YAGAMI INC.	